



**Catalogue**  
**CATERING**  
**Chapter**  
**REFRIGERATION**

**Model**  
**EAFN-1402 230V 1N 50Hz**

19037712

28/08/2019

**FREEZER CABINET SNACK, EAFN-1402**


- Constructed in AISI-304 stainless steel.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Height adjustable stainless steel legs.
- Inner LED lights.
- 50 mm, 40 kg/m<sup>3</sup> injected polyurethane insulation.
- Removable and height adjustable plastic covered steel shelves (17 Snack size levels) for easy cleaning. Equipment: 3 shelves per large door.
- Forced draught cooling system.
- Working temperature: from -18 °C to -22 °C. Ambient temperature: 43 °C (Except specific intensive usage).
- Number of doors: 2

**Options:**

- Locks.
- Castor kit (factory assembly).
- "- Stainless steel back panel.

**DIMENSIONS**

X Width	1388 mm	X Gross width	1470 mm
Y Depth	726 mm	Y Gross depth	800 mm
Z Height	2067 mm	Z Gross height	2084 mm
Net Weight	214,0 kg	Gross Weight	227,0 kg
Net volume	2,083 m <sup>3</sup>	Gross volume	2,451 m <sup>3</sup>



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	1,251 kW
Voltage	230V - 1N
Amperage	3,5 A
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-290
----------	-------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,735 kW
Annual elec. consumption	4855,00 kWh
Power consumption 24h	13,30 kWh
Gross internal volume	1109 L
Frozen net.vol	868 L
Climate class	4
Cooling gas load	138,000 g
Clasif. Energy efficiency	E
Energy Efficiency Index	84,48 %
Model type	Vertical cabinet

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T-6A
--------------------------	------------

Catalogue  
**CATERING**  
Chapter  
**REFRIGERATION**

Model  
**EAFN-1402 230V 1N 50Hz**

19037712

28/08/2019

