

HD70T



Refrigerator-GN2/1-anti-fingerprint-Shine New

One-piece structure in special anti-fingerprint steel. Single compartment, GN2/1. 1 door. Temperature ranges: 0/+10°C. Control panel with digital thermometer- thermostat. Ventilated refrigerating system. Automatic defrosting. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI SPA
Series	Shine - New
Supplier's model identifier	HD70T
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	E
Energy consumption E24, kW/h	3
Energy consumption/year, kW/h	1095
Method for energy consumption	EN 16825
Energy Efficiency Index	77,55
Net usable volume, lt	420
Volume, gross, lt	590
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R134a/1430
Refrigerant charge, kg	0,25

Refrigerator-GN2/1-anti-fingerprint-Shine New

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 23/08/2017



HD70T



LWA dB(A)	46
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	286
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,27

Construction features

Structure	one-piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Insulation thickness, mm	75
Door	1 door in special anti-fingerprint steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	10/120
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	12 plastic - coated hooks
Shelves (n.)	3, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	35

Dimensions and weights

Packaging dimension (LxDxH),cm	79x85,5x207
Exterior dimension (LxDxH), cm	75x83,5x204
Weight, packed, kg	128
Weight, kg	113

Refrigerator-GN2/1-anti-fingerprint-Shine New

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 23/08/2017

