



# LUXOR WHITE

Upright refrigerated display units



<b>Commercial Code</b>	<b>KD8QV</b>
<b>Temperature range</b>	-22/ +5°C
<b>Technical features</b>	<ul style="list-style-type: none"><li>• Display compartment in tempered glass throughout, with white screen-silk printed glass.</li><li>• Lower structure in extra clear white tempered glass</li><li>• A single compartment temperature to positive / negative</li><li>• Cooling unit at evaporation temperature -23.3°C and condensation temperature 53,5°C rated at 1140 W</li><li>• Climate Class 4, room +30°C and 55% R.H.</li><li>• Ventilated refrigeration obtained through evaporator fixed in the ceiling of the display compartment by means of an AISI 304 stainless steel structure</li><li>• Relative humidity: 65/40%</li><li>• Automatic defrosting by hot gas</li><li>• Anti-condense heating elements</li><li>• Ventilated system on the back with the air circulation not directed straight at food</li><li>• Refrigerant fluid: R404A</li><li>• Electronic panel control board with touch keys and HACCP alarms</li></ul>
<b>Functional features</b>	<ul style="list-style-type: none"><li>• Display shelves in tempered glass. possibility of loading up to 12 kg per shelf. On request available the accessoire KSR25KG: front bearing kit for shelves, to load up to 25 kg</li><li>• Easily removable magnetic gasket</li><li>• Glass door with “invisible” full-height handle</li><li>• Gross internal volume: 490 litri</li><li>• High brightness LED bar lighting, front panel on the back of the door and on internal ceiling element in the display compartment</li><li>• Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company</li><li>• Standard accessories: nr 5 display shelves in tempered glass with the back upright on AISI 304 stainless steel rack</li><li>• Integrated wheels, hidden by the structure. (nr 4)</li></ul>
<b>External size</b>	80.5x64.5x184cm
<b>Gross/Net weight</b>	243/267 kg
<b>Electrical power</b>	2 kW Standard connection: V-Hz 230V 1N-/50Hz