KFSD2B2



PASTRY FREEZER 60 x 80 cm, 2 DOORS

Exterior/interior AISI 304 18-10 st/steel. Ventil. cooling system with finned evaporator. Electronic

thermometer/thermostat.Automatic defrosting system by heating el.,automatic evaporation of condense drain.AISI304 18-10 s/s handle and removable shelf supports. Single compartment 60x80 cm, two doors.



CE

General information

Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSD2B2
Category	vertical cabinet
Туре	freezer
Line	pastry & bakery - EN 60x80
hnical features	
Temperature ranges, °C	-24/-12
Energy Efficiency Class	D
Energy consumption E24, kW/h	9,47
Energy consumption/year, kW/h	3457
Method for energy consumption	EN 16825
Energy Efficiency Index	71,56
Net usable volume, lt	603
Volume, gross, lt	852
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}$
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,3
LWA dB(A)	61
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary

PASTRY FREEZER 60 x 80 cm, 2 DOORS

SAGI S.P.A. con socio unico Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or error



KFSD2B2



Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	1054
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,22

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for opening inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

Dimensions and weights

U		
Packaging dimension (LxDxH),cm	89x106,5x213	
Exterior dimension (LxDxH), cm	82x100x204	_
Weight, packed, kg	198	-
Weight, kg	180	-

