

KFSD2N2

PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.



Exterior/interior in AISI304 18-10 s/steel. Ventil. cooling system with finned evaporator. Electronic thermometer/thermostat. Automatic defrosting system by hot gas, automatic evaporation of condense drain. AISI304 18-10 s/s handle and removable shelf supports. Single compartment 60x80 cm, two doors.



General information

Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSD2N2
Category	vertical cabinet
Type	refrigerator
Line	pastry & bakery - EN 60x80

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	G
Energy consumption E24, kW/h	5,07
Energy consumption/year, kW/h	1851
Method for energy consumption	EN 16825
Energy Efficiency Index	106,42
Net usable volume, lt	603
Volume, gross, lt	852
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,34
LWA dB(A)	56
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary

PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 30/08/2017



KFSD2N2



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	566
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,8

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

Dimensions and weights

Packaging dimension (LxDxH),cm	89x106,5x213
Exterior dimension (LxDxH), cm	82x100x204
Weight, packed, kg	183
Weight, kg	165

PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 30/08/2017

