KFSDR2B2

-



PASTRY FREEZER 60 x 80 cm, 2 DOORS

Exterior/interior AISI 304 18-10 st/steel. Ventil. cooling system with finned evaporator. Electronic

thermometer/thermostat.Automatic defrosting system by heating el.,automatic evapor.of condense drain. AISI304 18-10 s/s handle/removable shelf supports. 1 compartment 60 x 80, for remote cooling unit.



Note	absorption while defrosting
neral information	
Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSDR2B2
Category	vertical cabinet
Туре	freezer
Line	pastry & bakery - EN 60x80
hnical features	
Temperature ranges, °C	-24/-12
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only whe necessary
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,21

SAGI S.P.A. con socio unico

External material

Structure

AISI 304 stainless steel

one-piece structure with rounded internal corners

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy www.sagispa.it | info@sagispa.it



KFSDR2B2



Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

50			
	Key-lock	yes	
	Lighting	yes	
	Couple of guides (n.)	20 pair of AISI 304 stainless steel runners	
Di	mensions and weights		
	Packaging dimension (LxDxH),cm	89x106,5x213	
	Exterior dimension (LxDxH), cm	82x100x204	
	Weight, packed, kg	176	
	Weight, kg	158	

