

KFSE2B2

PASTRY FREEZER 60 x 80 cm, 2 DOORS

Exterior/interior AISI 304 18-10 st/St. Ventilated cooling system with finned evaporator. H.A.C.C.P. electronic control. 'Intelligent' defrosting system by heating el., automatic evaporation of condense drain. AISI304 18-10 s/s handle and removable shelf supports. Single compartment 60x80 cm, two doors.



General information

Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSE2B2
Category	vertical cabinet
Type	freezer
Line	pastry & bakery - EN 60x80

Technical features

Temperature ranges, °C	-24/-12
Energy Efficiency Class	D
Energy consumption E24, kW/h	9,47
Energy consumption/year, kW/h	3457
Method for energy consumption	EN 16825
Energy Efficiency Index	71,56
Net usable volume, lt	603
Volume, gross, lt	852
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,3
LWA dB(A)	61
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary

PASTRY FREEZER 60 x 80 cm, 2 DOORS

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 30/08/2017



KFSE2B2



Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	1054
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1,22

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	LCD with multilingual library
Alarms	visualise and memorise till 30 HACCP alarms
Functions/programs	Energy Saving - Setting of the relative humidity from 60% to 90%

Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

Dimensions and weights

Packaging dimension (LxDxH),cm	89x106,5x213
Exterior dimension (LxDxH), cm	82x100x204
Weight, packed, kg	185
Weight, kg	170

PASTRY FREEZER 60 x 80 cm, 2 DOORS

