# KFSER2B2

## PASTRY FREEZER 60 x 80 cm, 2 DOORS

Exterior/interior AISI 304 18-10 st/St. Ventilated cooling system with finned evaporator. H.A.C.C.P. electronic control.'Intelligent' defrosting system by heating el.,automatic evap.of condense drain. AISI304 18-10 s/s handle and remov.shelf supports. 1 compartm.60x80 suitable for remote cooling unit.



(€

Note	absorption while defrosting
neral information	
Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSER2B2
Category	vertical cabinet
Туре	freezer
Line	pastry & bakery - EN 60x80
hnical features	
Temperature ranges, °C	-24/-12
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only wher necessary
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,5

SAGI S.P.A. con socio unico

External material

Structure

**Construction features** 

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy





AISI 304 stainless steel

one-piece structure with rounded internal corners





# PASTRY FREEZER 60 x 80 cm, 2 DOORS

# KFSER2B2



Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155
rol and functions	
Kinf of control	electronic pannel control board
Display	LCD with multilingual library
Alarms	visualise and memorise till 30 HACCP alarms
Functions/programs	Energy Saving - Setting of the relative humidity from 60% to 90%
dard	
Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners
ensions and weights	
Packaging dimension (LxDxH),cm	89x106,5x213
Exterior dimension (LxDxH), cm	82x100x204

152



Weight, kg

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy