

# KFSER2N2



## PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.

Exterior/interior AISI 304 18-10 s/st. Ventilated cooling system with evaporator.H.A.C.C.P.electron. control panel. 'Intelligent' defrosting system by hot gas,autom.evaporation of condense drain. AISI304 18-10 s/s handle/removable shelf supports. 1 compartm.60x80 suitable for remote cooling unit.



Note	absorption while defrosting
------	-----------------------------

### General information

Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSER2N2
Category	vertical cabinet
Type	refrigerator
Line	pastry & bakery - EN 60x80

### Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,4

### Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel

PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.

#### SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 30/08/2017



# KFSER2N2



Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom with drain hole
Insulation thickness, mm	75
Door	2x1/2 doors in AISI 304 stainless steel
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	15/30 in the top compartment and 19/30 in the lower compartment
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

## Control and functions

Kinf of control	electronic pannel control board
Display	LCD with multilingual library
Alarms	visualise and memorise till 30 HACCP alarms
Functions/programs	Energy Saving - Setting of the relative humidity from 60% to 90%

## Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 pair of AISI 304 stainless steel runners

## Dimensions and weights

Packaging dimension (LxDxH),cm	89x106,5x213
Exterior dimension (LxDxH), cm	82x100x204
Weight, packed, kg	170
Weight, kg	150

PASTRY REFRIGERATOR 60x80 cm, 2 DOORS, POS.TEMP.

### SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

[www.sagispa.it](http://www.sagispa.it) | [info@sagispa.it](mailto:info@sagispa.it)

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 30/08/2017

