# KFSER2N

# **106**

## PASTRY REFRIGERATOR 60x80 cm, ONE DOOR, POS.TEMP.

Exterior/interior AISI 304 18-10 s/st. Ventilated cooling system with evaporator.H.A.C.C.P.electron. control panel. 'Intelligent' defrosting system by hot gas,autom.evaporation of condense drain. AISI304 18-10 s/s handle/removable shelf supports. Compartm.60 x 80 suitable for remote cooling unit.



( (

Note	absorption while defrosting
	absorption write defrosting
eral information	
Supplier/producer 's name	SAGI SPA
Series	Pastry & Bakery
Supplier's model identifier	KFSER2N
Category	vertical cabinet
Туре	refrigerator
Line	pastry & bakery - EN 60x80
nnical features	
Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Method for energy consumption	EN 16825
Climate class	5 (+40°C, 40% R.H.)
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only whe necessary
Evaporation of condense drain	automatic
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,4
struction features	
Structure	one-piece structure with rounded internal corners

SAGI S.P.A. con socio unico

External material

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy

AISI 304 stainless steel





# KFSER2N



NI JENZIA		
Internal material	AISI 304 stainless steel diamond treated bottom with drain hole	
Internal bottom		
Insulation thickness, mm	75	
Door	1 door in AISI 304 stainless steel	
Standard hinging door	on the right / reversible on the site with self-closing device for openings inferior to 90°	
Door handle	integrated full-height	
Internal structure	AISI 304 stainless steel grid-supporting rack	
Positions (n.)/spaced, mm	40/30	
Evaporator	positioned outside the compartment	
Easymaintenance	accessibility to all the functional and control components via a retractable front panel	
Safety interlock switch	yes, to stop internal fan and switch on compartment light	
Feet	stainless steel AISI 304, adjustable in height	
Height of feet, mm	105 ÷ 155	
ntrol and functions		
Kinf of control	electronic pannel control board	
Display	LCD with multilingual library	
Alarms	visualise and memorise till 30 HACCP alarms	

Kinf of control	electronic pannel control board
Display	LCD with multilingual library
Alarms	visualise and memorise till 30 HACCP alarms
Functions/programs	Energy Saving - Setting of the relative humidity from 60% to 90%

### Standard

Key-lock	yes
Lighting	yes
Couple of guides (n.)	20 nair of AISL 304 stainless steel runners

#### **Dimensions and weights**

Packaging dimension (LxDxH),cm	89x106,5x213
Exterior dimension (LxDxH), cm	82x100x204
Weight, packed, kg	170
Weight, kg	150



