

KIGBA



Refrigerated counter-GN1/1-AISI 304-I-green

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1.3 doors. Control panel with electronic circuit board with special functions. Automatic defrosting electric type.



General information

Supplier/producer 's name	SAGI SPA
Series	I-GREEN
Supplier's model identifier	KIGBA
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	-2/+10
Energy Efficiency Class	A
Energy consumption E24, kW/h	1,644
Energy consumption/year, kW/h	600
Method for energy consumption	EN 16825
Energy Efficiency Index	24,9
Net usable volume, lt	241
Volume, gross, lt	434
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R134a/1430
Refrigerant charge, kg	0,39
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic by heating elements

Refrigerated counter-GN1/1-AISI 304-I-green

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 11/09/2017



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	457
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,37

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Equipped with	3 doors

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Functions/programs	Hyper Cold - Energy Saving - setting of the relative humidity to 75% or to 90%

Standard

Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packaging dimension (LxDxH),cm	192x76x100
Exterior dimension (LxDxH), cm	185x70x98,5
Weight, packed, kg	150
Weight, kg	138