KIRC2A

JOGI

Refrigerated counter-for remote unit-GN1/1-Idea

One-piece AISI 304 stainless steel body. Temperature ranges: -2/+8°C. Preset for remote cooling unit. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 70 cm. GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat.



 ϵ

Note	*absorption while defrosting
eral information	
Supplier/producer 's name	SAGI SPA
Series	Idea
Supplier's model identifier	KIRC2A
Category	counter cabinet
Туре	refrigerated counter
Line	catering - GN 1/1

Technical features

chinear reacares	
Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Net usable volume, lt	298
Volume, gross, lt	576
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R404A/3922
LWA dB(A)	20
Cooling system	ventilated refrigeration system
Defrosting	automatic by heating elements
Evaporation of condense drain	drainage underneath cooling unit compartment
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

Refrigerated counter-for remote unit-GN1/1-Idea





Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Equipped with	doors and drawers
Drawers, type: 1/2	2

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	ontical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packaging dimension (LxDxH),cm	210x75,5x100
Exterior dimension (LxDxH), cm	205x70x98,5
Weight, packed, kg	168
Weight, kg	153