



SYRIO

Upright refrigerated display case



Commercial Code	KP9R
Temperature range	+2/ +10°C
Technical features	<ul style="list-style-type: none"> • Unique and innovative cylindrical display compartment in tempered glass throughout, externally screen-silk printed • Base made in special anti-fingerprint stainless steel • One refrigerated room • Cooling unit at evaporation temperature -10 °C and condensation temperature 53,5°C rated at 1120 W • Climate Class 4, room +30°C and 55% R.H. • Ventilated refrigeration obtained through the evaporator being positioned in the lower part of the structure • Relative humidity: 70% • Automatic defrosting by air, every 6 hours, automatic evaporation of condense drain • Ventilated system on the back with the air circulation not directed straight at food • Refrigerant fluid: R404A • Electronic panel control board with touch keys and HACCP alarms (high/low temperature, probes failure, open door and black out)
Functional features	<ul style="list-style-type: none"> • Tempered glass shelves with rotation system, for maximum convenience and flexibility of use. Possibility of loading up to 15 kg per shelf • Easily removable magnetic gasket • Glass door with “invisible” full-height handle • Gross internal volume: 790lt • LED lighting • Installation allowed to an altitude up to 800 meters above sea level. For installation over 800, contact the company • Standard accessories: nr 5 tempered glass shelves (dimensions: ø 71cm) on AIS 304 stainless steel rack bars • Hidden integrated wheels (nr 6 with 4 feet)
External size	ø 95.6 x 183.4 h cm
Gross/Net weight	281/306kg
Electrical power	1 kW Standard connection: V-Hz 230V 1N-/50Hz