

Refrigerated counter-for cooking appliances-Snack

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Without top. GN 1/1.2 doors. Control panel with digital thermometer - thermostat. Refrigerated counters to support modular cooking appliances.



General information

| | |
|-----------------------------|----------------------|
| Supplier/producer 's name | SAGI SPA |
| Series | Snack |
| Supplier's model identifier | KSA |
| Category | counter cabinet |
| Type | refrigerated counter |
| Line | catering - GN 1/1 |

Technical features

| | |
|-------------------------------|--|
| Temperature ranges, °C | 0/+10 |
| Energy Efficiency Class | C |
| Energy consumption E24, kW/h | 2,75 |
| Energy consumption/year, kW/h | 1004 |
| Method for energy consumption | EN 16825 |
| Energy Efficiency Index | 45,54 |
| Net usable volume, lt | 93 |
| Volume, gross, lt | 195 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 °C |
| Refrigerant/GWP | R404A/3922 |
| Refrigerant charge, kg | 0,28 |
| LWA dB(A) | 46 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic |
| Evaporation of condense drain | automatic |

Refrigerated counter-for cooking appliances-Snack

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 25/09/2017



| | |
|--------------------------------|-----------------|
| Refrigeration power at -10°C W | 304 |
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,3 |

Construction features

| | |
|---------------------------|---|
| Structure | one-piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | press-formed bottom with drain hole |
| Insulation thickness, mm | 55 |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 7/40 |
| Evaporator | with an anti-corrosion treatment |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Worktop | without worktop |
| Equipped with | 2 doors |

Control and functions

| | |
|-----------------|------------------------|
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |

Standard

| | |
|------------------------------|--|
| Shelf's dimensions, cm | 32,5x53 GN1/1 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |

Dimensions and weights

| | |
|--------------------------------|-----------|
| Packaging dimension (LxDxH),cm | 147x76x75 |
| Exterior dimension (LxDxH), cm | 140x69x57 |
| Weight, packed, kg | 91 |
| Weight, kg | 81 |