KSB2M



Refrigerated counter-for cooking appliances-Snack

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C.GN 1/1. With doors and drawers. Control panel with digital thermometer - thermostat. Refrigerated counters to support modular cooking appliances.



 ϵ

General information

| Supplier/producer 's name | SAGI SPA |
|-----------------------------|----------------------|
| Series | Snack |
| Supplier's model identifier | KSB2M |
| Category | counter cabinet |
| Туре | refrigerated counter |
| Line | catering - GN 1/1 |

Technical features

| Temperature ranges, °C | 0/+10 |
|-------------------------------|--|
| Energy Efficiency Class | С |
| Energy consumption E24, kW/h | 2,85 |
| Energy consumption/year, kW/h | 1040 |
| Method for energy consumption | EN 16825 |
| Energy Efficiency Index | 45,33 |
| Net usable volume, It | 126 |
| Volume, gross, lt | 289 |
| Climate class | 5 (+40°C, 40% R.H.) |
| Heavy duty cabinets | This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$ |
| Refrigerant/GWP | R404A/3922 |
| Refrigerant charge, kg | 0,28 |
| LWA dB(A) | 46 |
| Cooling system | ventilated refrigeration system |
| Defrosting | automatic |
| Evaporation of condense drain | automatic |
| | |

IONet



Refrigerated counter-for cooking appliances-Snack

KSB2M



| Refrigeration power at -10°C W | 304 |
|--------------------------------|--|
| Frequency/voltage | 230V 1N~ / 50Hz |
| Electric power, kW | 0,3 |
| onstruction features | |
| Structure | one-piece structure with rounded internal corners |
| External material | AISI 304 stainless steel |
| Internal material | AISI 304 stainless steel |
| Internal bottom | press-formed bottom with drain hole |
| Insulation thickness, mm | 55 |
| Internal structure | AISI 304 stainless steel grid-supporting rack |
| Positions (n.)/spaced, mm | 7/40 |
| Evaporator | with an anti-corrosion treatment |
| Feet | stainless steel AISI 304, adjustable in height |
| Height of feet, mm | 140 ÷ 200 |
| Worktop | worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining |
| Equipped with | doors and drawers |
| Drawers, type: 1/2 - Snack | 2 |
| ontrol and functions | |
| Kinf of control | thermometer-thermostat |
| Display | digital |
| Alarms | optical and acoustical |
| tandard | |
| Shelf's dimensions, cm | 32,5x53 GN1/1 |
| Shelves and couple of guides | complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio |
| imensions and weights | |
| Packaging dimension (LxDxH),cm | 192x76x81 |
| Exterior dimension (LxDxH), cm | 185x70x63 |
| Weight, packed, kg | 154 |
| | |

142

Refrigerated counter-for cooking appliances-Snack



Weight, kg