

KSBM



Refrigerated counter-for cooking appliances-Snack

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. GN 1/1.3 doors. Control panel with digital thermometer - thermostat. Refrigerated counters to support modular cooking appliances.



General information

Supplier/producer 's name	SAGI SPA
Series	Snack
Supplier's model identifier	KSBM
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption E24, kW/h	2,85
Energy consumption/year, kW/h	1040
Method for energy consumption	EN 16825
Energy Efficiency Index	44,59
Net usable volume, lt	140
Volume, gross, lt	291
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,28
LWA dB(A)	46
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

Refrigerated counter-for cooking appliances-Snack

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 25/09/2017



Refrigeration power at -10°C W	304
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	press-formed bottom with drain hole
Insulation thickness, mm	55
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	7/40
Evaporator	with an anti-corrosion treatment
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Equipped with	3 doors

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical

Standard

Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packaging dimension (LxDxH),cm	192x76x81
Exterior dimension (LxDxH), cm	185x70x63
Weight, packed, kg	142
Weight, kg	130