

KUA2



Refrigerated counter-GN1/1-AISI 304-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Without top. Depth 70 cm. GN 1/1. With door and drawers. Control panel with digital thermometer - thermostat.



General information

Supplier/producer 's name	SAGI SPA
Series	Universal
Supplier's model identifier	KUA2
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption E24, kW/h	2,85
Energy consumption/year, kW/h	1040
Method for energy consumption	EN 16825
Energy Efficiency Index	44,71
Net usable volume, lt	137
Volume, gross, lt	288
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,28
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-GN1/1-AISI 304-Universal

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 05/09/2017



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	304
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,27

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	without worktop
Equipped with	door and drawers
Drawers, type: 1/2	2

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packaging dimension (LxDxH),cm	146x76x90
Exterior dimension (LxDxH), cm	140x70x84
Weight, packed, kg	108
Weight, kg	98