KUEAM

Refrigerated counter-GN1/1-antifingerprint-Twin

All-in-one structure in special anti-fingerprint steel.Temperature ranges: 0/+10°C.Worktop 60 mm thick in AISI 304 stainless steel.Depth 70 cm.GN 1/1.2 doors.Control panel with digital thermometer - thermostat.

General information

Supplier/producer 's name	SAGI SPA
Series	Twin
Supplier's model identifier	KUEAM
Category	counter cabinet
Type	refrigerated counter
Line	catering - GN 1/1

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption E24, kW/h	2,85
Energy consumption/year, kW/h	1040
Method for energy consumption	EN 16825
Energy Efficiency Index	43,5
Net usable volume, lt	161
Volume, gross, lt	286
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,28
LWA dB(A)	46
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

SAGI S.P.A. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy
www.sagispa.it | info@sagispa.it
Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

KUEAM

Evaporation of condense drain	automatic
Refrigeration power at -10°C W	304
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,3

Construction features

Structure	one-piece structure with rounded internal corners
External material	special anti-fingerprint steel
Internal material	special anti-fingerprint steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining
Equipped with	2 doors

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x53 GN1/1
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf GN1/1 per sectio

Dimensions and weights

Packaging dimension (LxDxH),cm	146x76x90
Exterior dimension (LxDxH), cm	140x70x90
Weight, packed, kg	117
Weight, kg	107

SAGI S.P.A. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno – Italy
www.sagispa.it | info@sagispa.it
Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.