

KUJB2A



Refrigerated counter-Depth 60cm-Universal

One-piece AISI 304 stainless steel body. Temperature ranges: 0/+10°C. Worktop 60 mm thick in AISI 304 stainless steel with splashback 85 mm. Depth 60 cm. For shelves 32,5x46 cm. With doors and drawers. Control panel with digital thermometer - thermostat.



General information

Supplier/producer 's name	SAGI SPA
Series	Universal
Supplier's model identifier	KUJB2A
Category	counter cabinet
Type	refrigerated counter
Line	catering - depth 60 cm

Technical features

Temperature ranges, °C	0/+10
Energy Efficiency Class	C
Energy consumption E24, kW/h	3,18
Energy consumption/year, kW/h	1161
Method for energy consumption	EN 16825
Energy Efficiency Index	46,93
Net usable volume, lt	190
Volume, gross, lt	357
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,32
LWA dB(A)	50
Cooling system	ventilated refrigeration system. U- flow air circulation to assure peak cooling unit reliability
Defrosting	automatic

Refrigerated counter-Depth 60cm-Universal

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 07/09/2017



Evaporation of condense drain	automatic
Refrigeration power at -10°C W	486
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,43

Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	60
Internal structure	AISI 304 stainless steel grid-supporting rack
Positions (n.)/spaced, mm	11/40,5
Evaporator	with an anti-corrosion treatment
Easymaintenance	the cooling unit pulls out to simplify routine cleaning of the condenser
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	140 ÷ 200
Worktop	worktop 60 mm thick in AISI 304 stainless steel (8/10mm), with soundproofing lining; with splashbac
Equipped with	doors and drawers
Drawers, type: 1/2	2

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical

Standard

Key-lock	optional
Shelf's dimensions, cm	32,5x46
Shelves and couple of guides	complete with 1 pair of AISI 304 stainless steel runners and 1 plastic-coated shelf for section

Dimensions and weights

Packaging dimension (LxDxH),cm	192x66x100
Exterior dimension (LxDxH), cm	185x60x98,5
Weight, packed, kg	150
Weight, kg	138

Refrigerated counter-Depth 60cm-Universal