ME150BT

JOGI

Freezer-GN2/1-AISI 304-Nex-to

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 2 doors. Temperature ranges: -20/-10°C. Control panel with digital thermometer- thermostat. Ventilated refrigerating system. Automatic defrosting. Lighting and key-operated lock.



 ϵ

General information

Supplier/producer 's name	SAGI SPA
Series	Nex-to
Supplier's model identifier	ME150BT
Category	vertical cabinet
Туре	freezer
Line	catering - GN 2/1

Technical features

chinical reactives	
Temperature ranges, °C	-20/-10
Energy Efficiency Class	G
Energy consumption E24, kW/h	18,54
Energy consumption/year, kW/h	6767
Method for energy consumption	EN 16825
Energy Efficiency Index	114,98
Net usable volume, lt	960
Volume, gross, lt	1150
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 $^{\circ}\text{C}$
Refrigerant/GWP	R404A/3922
Refrigerant charge, kg	0,45
LWA dB(A)	60
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic

Freezer-GN2/1-AISI 304-Nex-to





ME150BT



Refrigeration power -23,3°C W	1054
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	1
nstruction features	
Structure	one-piece structure with rounded internal corners
External material	AlSI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	with an anti-corrosion treatment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165
ntrol and functions	
Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical and acoustical
ndard	
Key-lock	yes
Lighting	yes
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60
nensions and weights	
Packaging dimension (LxDxH),cm	145x85,5x207
Exterior dimension (LxDxH), cm	139x83,5x204
Weight, packed, kg	230
Weight, kg	210