

ME150LTR



Refrigerator-Remote-press-formed sidesGN2/1-Nex-to

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Refrigerator remote. Single compartment, GN2/1. 2 doors. Temperature ranges: -2/+8°C. Control panel with digital thermometer- thermostat. Ventilated refrigerating system. Automatic defrosting electric type. Lighting and key-operated lock.



Note	absorption while defrosting
------	-----------------------------

General information

Supplier/producer 's name	SAGI SPA
Series	Nex-to
Supplier's model identifier	ME150LTR
Category	vertical cabinet
Type	refrigerator
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-2/+8
Energy Efficiency Class	product are excluded from the European energy classification label according to EU Regulation 2015/1
Net usable volume, lt	800
Volume, gross, lt	1150
Climate class	5 (+40°C, 40% R.H.)
Refrigerant/GWP	R134a/1430
LWA dB(A)	50
Cooling system	ventilated refrigeration system
Defrosting	automatic
Evaporation of condense drain	automatic
Refrigeration power at -10°C W	462
Frequency/voltage	230V 1N~ / 50 ÷ 60Hz
Electric power, kW	0,8

Refrigerator-Remote-press-formed sidesGN2/1-Nex-to

SAGI S.P.A. con socio unico
Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy
www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 29/08/2017



Construction features

Structure	one-piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	with rounded corners
Insulation thickness, mm	75
Door	2 doors in AISI 304 stainless steel
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	with an anti-corrosion treatment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	115 ÷ 165

Control and functions

Kinf of control	thermometer-thermostat
Display	digital
Alarms	optical

Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	6, plastic coated
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

Dimensions and weights

Packaging dimension (LxDxH),cm	145x85,5x207
Exterior dimension (LxDxH), cm	139x83,5x204
Weight, packed, kg	200
Weight, kg	180