

XE70B

Freezer-press-formed sides GN2/1-X-treme

One-piece structure in AISI 304 stainless steel. The storage chamber consists of AISI 304 stainless steel press-formed internal sides, 20 positions spaced 55cm. Single compartment, GN2/1. 1 door. Temperature ranges: -22/-15°C. Electronic control panel. Fan-assisted refrigeration with external evaporator. High efficiency motor unit. Automatic defrosting electric type. Lighting and key-operated lock.



General information

Supplier/producer 's name	SAGI SPA
Series	X-TREME
Supplier's model identifier	XE70B
Category	vertical cabinet
Type	freezer
Line	catering - GN 2/1

Technical features

Temperature ranges, °C	-22/-15
Energy Efficiency Class	C
Energy consumption E24, kW/h	4,15
Energy consumption/year, kW/h	1394
Method for energy consumption	EN 16825
Energy Efficiency Index	38,1
Net usable volume, lt	444
Volume, gross, lt	521
Climate class	5 (+40°C, 40% R.H.)
Heavy duty cabinets	This appliance is intended for use in ambient temperatures up to 40 °C
Refrigerant/GWP	R290/3
Refrigerant charge, kg	0,120
LWA dB(A)	39
Cooling system	ventilated refrigeration system
Defrosting	automatic "intelligent" defrosting by hot gas, which activates only when necessary

Freezer-press-formed sides GN2/1-X-treme

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

1/2 PRINTED 29/08/2017



XE70B



Evaporation of condense drain	automatic
Refrigeration power -23,3°C W	611
Frequency/voltage	230V 1N~ / 50Hz
Electric power, kW	0,67

Construction features

Structure	one - piece structure with rounded internal corners
External material	AISI 304 stainless steel
Internal material	AISI 304 stainless steel
Internal bottom	diamond treated bottom
Insulation thickness, mm	75
Door	1 door in AISI 304 stainless steel
Standard hinging door	on the right/reversible on the site with self-closing device for openings inferior to 90°
Door handle	integrated full-height
Internal structure	with press-formed internal sides in AISI 304 stainless steel
Positions (n.)/spaced, mm	20/55
Evaporator	positioned outside the compartment
Easymaintenance	accessibility to all the functional and control components via a retractable front panel
Safety interlock switch	yes, to stop internal fan and switch on compartment light
Feet	stainless steel AISI 304, adjustable in height
Height of feet, mm	105 ÷ 155

Control and functions

Kinf of control	electronic pannel control board
Display	digital
Alarms	optical and acoustical
Functions/programs	Hyper Cold, Energy Saving

Standard

Key-lock	yes
Lighting	yes
Shelves (n.)	4 stainless steel AISI304
Shelf's dimensions, cm	53x65 (GN 2/1)
Shelf loading capacity, kg	60

Dimensions and weights

Packaging dimension (LxDxH),cm	75,5x85,5x213
Exterior dimension (LxDxH), cm	68,4x80x204
Weight, packed, kg	140
Weight, kg	125

Freezer-press-formed sides GN2/1-X-treme

SAGI S.P.A. con socio unico

Zona Industriale Campolungo, 79/81 - 63100 Ascoli Piceno - Italy

www.sagispa.it | info@sagispa.it

Sagi Spa reserves the right to make product changes and cannot be held responsible for omissions and/or errors.

2/2 PRINTED 29/08/2017

