

# SL 280



## FROZEN DICE



### Self-contained ice maker up to 134 kg - Sprayer system

#### • Position n°




#### • Application fields

Hotel	●●●●●●●●●●	Fish market	●●●●●●●●●●
Restaurant	●●●●●●●●●●	Supermarket	●●●●●●●●●●
Fast food	●●●●●●●●●●	SPA	●●●●●●●●●●
Bar	●●●●●●●●●●	Medical	●●●●●●●●●●
Disco	●●●●●●●●●●	Industry	●●●●●●●●●●

#### • Features & Plus

- Full cube, compact and crystalline
- External structure AISI 304 Scotch Brite
- Adjustable Stainless Steel feet
- Removable and cleanable air filter
- Electromechanical functioning
- Air Cooling and Water Cooling systems
- Standard and special voltages
- Insulated retractable door
- ON-OFF switch
- Internal bin insulation HCFC free
- Conformity to RoHS directive
- Easy cleaning thanks to rounded surfaces
- Model in Tropical Class + 43 ° C

#### • Available dice size



#### • Prod. 24h

Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	134
21° C	15° C	130
32° C	21° C	106

**2 Years Warranty**

subject to limitations

#### • Certifications available for this model



**N.T.F. S.r.l. Nuove Tecnologie del Freddo**

Via dell'Industria 10/B tel. +39 0331 436217  
20020 Villa Cortese (MI), Italy fax +39 0331 436218

[www.ntfice.it](http://www.ntfice.it)  
[info@ntfice.it](mailto:info@ntfice.it)



ntfice.it




# SL 280



## FROZEN DICE



### Self-contained ice maker up to 134 kg - Sprayer system



#### • Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

- ① Water inlet:  
141 mm - 290 mm - 3/4"
- ② Water outlet:  
79 mm - 245 mm - 24 mm
- ③ Electrical connection:  
186 mm - 326 mm

#### • Working conditions

- Location: Indoor

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

#### • Technical information

Production in 24h	130 kg
Store capacity, up to	65 kg
Cooling system	A - W
Kind of cube	14-17-32-41-60 g
Refrigerant	R404A
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	1050 W
Fuse	16 A
Water consumption	A: 2,8 l/kg W: 15,3 l/kg
Sizes (L-P-H mm)	840 - 740 - 1075
Sizes with pack (L-P-H mm)	880 - 785 - 1245
Net weight	113 kg
Gross weight	133 kg
Finish	AISI 304 stainless steel, scotch brite

All the technical information must be considered at the following conditions:

Sizes without feet	Standard Cube (17 g)	Ambient temperature +21° C	Water temperature +15° C	Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice  
Rev. 00 - Issued January 2017



**N.T.F. S.r.l. Nuove Tecnologie del Freddo**

Via dell'Industria 10/B tel. +39 0331 436217  
20020 Villa Cortese (MI), Italy fax +39 0331 436218

[www.ntfice.it](http://www.ntfice.it)  
info@ntfice.it



ntfice.it

